

Foundations of Artificial Intelligence

B10. State-Space Search: Analysis of Heuristics

Malte Helmert

University of Basel

March 18, 2026

Foundations of Artificial Intelligence

March 18, 2026 — B10. State-Space Search: Analysis of Heuristics

B10.1 Properties of Heuristics

B10.2 Examples

B10.3 Connections

B10.4 Summary

State-Space Search: Overview

Chapter overview: state-space search

- ▶ B1–B3. Foundations
- ▶ B4–B8. Basic Algorithms
- ▶ B9–B15. Heuristic Algorithms
 - ▶ B9. Heuristics
 - ▶ B10. Analysis of Heuristics
 - ▶ B11. Best-first Graph Search
 - ▶ B12. Greedy Best-first Search, A^* , Weighted A^*
 - ▶ B13. IDA*
 - ▶ B14. Properties of A^* , Part I
 - ▶ B15. Properties of A^* , Part II

Reminder: Heuristics

Definition (heuristic)

Let \mathcal{S} be a state space with states S .

A **heuristic function** or **heuristic** for \mathcal{S} is a function

$$h : \mathcal{S} \rightarrow \mathbb{R}_0^+ \cup \{\infty\},$$

mapping each state to a nonnegative number (or ∞).

B10.1 Properties of Heuristics

Perfect Heuristic

Definition (perfect heuristic)

Let \mathcal{S} be a state space with states S .

The **perfect heuristic** for \mathcal{S} , written h^* , maps each state $s \in \mathcal{S}$

- ▶ to the cost of an **optimal solution** for s , or
- ▶ to ∞ if no solution for s exists.

German: perfekte Heuristik

Properties of Heuristics


Definition (safe, goal-aware, admissible, consistent)

Let \mathcal{S} be a state space with states S .

A heuristic h for \mathcal{S} is called

- ▶ **safe** if $h^*(s) = \infty$ for all $s \in \mathcal{S}$ with $h(s) = \infty$
- ▶ **goal-aware** if $h(s) = 0$ for all goal states s
- ▶ **admissible** if $h(s) \leq h^*(s)$ for all states $s \in \mathcal{S}$
- ▶ **consistent** if $h(s) \leq \text{cost}(a) + h(s')$ for all transitions $s \xrightarrow{a} s'$

German: sicher, zielerkennend, zulässig, konsistent



B10.2 Examples

Properties of Heuristics: Examples

Which of our three example heuristics have which properties?

Route Planning in Romania

straight-line distance:

- ▶ safe
- ▶ goal-aware
- ▶ admissible
- ▶ consistent

Why?

Properties of Heuristics: Examples

Which of our three example heuristics have which properties?

Blocks World

misplaced blocks:

- ▶ safe?
- ▶ goal-aware?
- ▶ admissible?
- ▶ consistent?

Properties of Heuristics: Examples

Which of our three example heuristics have which properties?

Missionaries and Cannibals

people on wrong river bank:

- ▶ safe?
- ▶ goal-aware?
- ▶ admissible?
- ▶ consistent?

B10.3 Connections

Properties of Heuristics: Connections (1)

Theorem (admissible \implies safe + goal-aware)

Let h be an admissible heuristic.

Then h is safe and goal-aware.

Why?

Properties of Heuristics: Connections (2)

Theorem (goal-aware + consistent \implies admissible)

Let h be a goal-aware and consistent heuristic.

Then h is admissible.

Why?

Showing All Four Properties

How can one show most easily that a heuristic has all four properties?

B10.4 Summary

Summary

- ▶ **perfect heuristic h^*** : true cost to the goal
- ▶ important properties: **safe, goal-aware, admissible, consistent**
- ▶ **connections** between these properties
 - ▶ admissible \implies safe and goal-aware
 - ▶ goal-aware and consistent \implies admissible