

Discrete Mathematics in Computer Science

Introduction to Formal Logic

Malte Helmert, Gabriele Röger

University of Basel

Why Logic?

- formalizing mathematics
 - What is a true statement?
 - What is a valid proof?
- basis of many tools in computer science
 - design of digital circuits
 - semantics of databases; query optimization
 - meaning of programming languages
 - verification of safety-critical hardware/software
 - knowledge representation in artificial intelligence
 - logic-based programming languages (e.g. Prolog)
 - ...

Application: Logic Programming I

Declarative approach: Describe **what** to accomplish,
not how to accomplish it.

Application: Logic Programming II

Prolog program

```
color(red). color(blue). color(green). color(yellow).

neighbor(StateAColor, StateBColor) :-
    color(StateAColor), color(StateBColor),
    StateAColor \= StateBColor.

switzerland(AG, AI, AR, BE, BL, BS, FR, GE, GL, GR,
            JU, LU, NE, NW, OW, SG, SH, SO, SZ, TG,
            TI, UR, VD, VS, ZG, ZH) :-
    neighbor(AG, BE), neighbor(AG, BL), neighbor(AG, LU),
    ...
    neighbor(UR, VS), neighbor(VD, VS), neighbor(ZH, ZG).
```

What Logic is About

General Question:

- Given some knowledge about the world (a **knowledge base**)
- what can we **derive** from it?
- And on what basis may we argue?

⇒ **logic**

Goal: “mechanical” proofs

- formal “game with letters”
- detached from a concrete meaning

Task

What's the secret of your long life?



I am on a strict diet: If I don't drink beer to a meal, then I always eat fish. Whenever I have fish and beer with the same meal, I abstain from ice cream. When I eat ice cream or don't drink beer, then I never touch fish.

Simplify this advice!

Propositional Logic

Propositional logic is a simple logic without numbers or objects.

Building blocks of propositional logic:

- **propositions** are statements that can be either true or false
- **atomic propositions** cannot be split into sub-propositions
- **logical connectives** connect propositions to form new ones

German: Aussagenlogik, Aussage, atomare Aussage, Junktoren

Examples for Building Blocks



If I don't drink beer to a meal, then I always eat fish. Whenever I have fish and beer with the same meal, I abstain from ice cream. When I eat ice cream or don't drink beer, then I never touch fish.

- Every sentence is a proposition that consists of sub-propositions (e. g., “eat ice cream or don't drink beer”).

Examples for Building Blocks



If I don't **drink beer** to a meal, then I always **eat fish**. Whenever I **have fish** and **beer** with the same meal, I abstain from **ice cream**. When I **eat ice cream** or don't **drink beer**, then I never touch **fish**.

- Every sentence is a proposition that consists of sub-propositions (e. g., “eat ice cream or don't drink beer”).
- atomic propositions “**drink beer**”, “**eat fish**”, “**eat ice cream**”

Examples for Building Blocks



If I don't drink beer to a meal, then I always eat fish. Whenever I have fish and beer with the same meal, I abstain from ice cream. When I eat ice cream or don't drink beer, then I never touch fish.

- Every sentence is a proposition that consists of sub-propositions (e. g., “eat ice cream or don't drink beer”).
- atomic propositions “drink beer”, “eat fish”, “eat ice cream”
- logical connectives “and”, “or”, negation, “if, then”

Problems with Natural Language



If I don't drink beer to a meal, then I always eat fish.

Whenever I have fish and beer with the same meal, I abstain from ice cream.

When I eat ice cream or don't drink beer, then I never touch fish.

Problems with Natural Language



If I don't drink beer **to a meal**, then I **always** eat fish.

Whenever I have fish and beer **with the same meal**, I abstain from ice cream.

When I eat ice cream or don't drink beer, then I never touch fish.

- **“irrelevant” information**

Problems with Natural Language



If I don't drink beer, then I eat fish.
Whenever I have fish and beer, I abstain
from ice cream.

When I eat ice cream or don't drink
beer, then I never touch fish.

- “irrelevant” information

Problems with Natural Language



If I **don't** drink beer, then I eat fish.
Whenever I have fish and beer, I **abstain**
from ice cream.
When I eat ice cream or **don't** drink
beer, then I **never** touch fish.

- “irrelevant” information
- **different formulations for the same connective/proposition**

Problems with Natural Language



If I don't drink beer, then I **eat fish**.
Whenever I **have fish** and beer, I abstain
from ice cream.
When I eat ice cream or don't drink
beer, then I never **touch fish**.

- “irrelevant” information
- **different formulations for the same** connective/**proposition**

Problems with Natural Language



If not DrinkBeer, then EatFish.
If EatFish and DrinkBeer,
then not EatIceCream.
If EatIceCream or not DrinkBeer,
then not EatFish.

- “irrelevant” information
- different formulations for the same connective/proposition

What is Next?

- What are meaningful (well-defined) sequences of atomic propositions and connectives?
“if then EatIceCream not or DrinkBeer and” not meaningful
→ **syntax**
- What does it mean if we say that a statement is true?
Is “DrinkBeer and EatFish” true?
→ **semantics**
- When does a statement logically follow from another?
Does “EatFish” follow from “if DrinkBeer, then EatFish”?
→ **logical entailment**

German: Syntax, Semantik, logische Folgerung

Discrete Mathematics in Computer Science

Syntax of Propositional Logic

Malte Helmert, Gabriele Röger

University of Basel

Syntax of Propositional Logic

Definition (Syntax of Propositional Logic)

Let A be a set of **atomic propositions**. The set of **propositional formulas** (over A) is inductively defined as follows:

- Every **atom** $a \in A$ is a propositional formula over A .
- If φ is a propositional formula over A , then so is its **negation** $\neg\varphi$.
- If φ and ψ are propositional formulas over A , then so is the **conjunction** $(\varphi \wedge \psi)$.
- If φ and ψ are propositional formulas over A , then so is the **disjunction** $(\varphi \vee \psi)$.

The **implication** $(\varphi \rightarrow \psi)$ is an abbreviation for $(\neg\varphi \vee \psi)$.

The **biconditional** $(\varphi \leftrightarrow \psi)$ is an abbrev. for $((\varphi \rightarrow \psi) \wedge (\psi \rightarrow \varphi))$.

German: atomare Aussage, aussagenlogische Formel, Atom, Negation, Konjunktion, Disjunktion, Implikation, Bikonditional

Syntax: Examples

Which of the following sequences of symbols are propositional formulas over the set of all possible letter sequences? Which kinds of formula are they (atom, conjunction, ...)?

- $(A \wedge (B \vee C))$
- $((\text{EatFish} \wedge \text{DrinkBeer}) \rightarrow \neg \text{EatIceCream})$
- $\neg(\wedge \text{Rain} \vee \text{StreetWet})$
- $\neg(\text{Rain} \vee \text{StreetWet})$
- $\neg(A = B)$
- $(A \wedge \neg(B \leftrightarrow)C)$
- $(A \vee \neg(B \leftrightarrow C))$
- $((A \leq B) \wedge C)$
- $((A_1 \wedge A_2) \vee \neg(A_3 \leftrightarrow A_2))$

Discrete Mathematics in Computer Science

Semantics of Propositional Logic

Malte Helmert, Gabriele Röger

University of Basel

Meaning of Propositional Formulas?

So far propositional formulas are only symbol sequences without any meaning.

For example, what does this mean:

$((\text{EatFish} \wedge \text{DrinkBeer}) \rightarrow \neg \text{EatIceCream})?$

▷ We need semantics!

Semantics of Propositional Logic

Definition (Semantics of Propositional Logic)

A **truth assignment** (or **interpretation**) for a set of atomic propositions A is a function $\mathcal{I} : A \rightarrow \{0, 1\}$.

A propositional **formula** φ (over A) **holds under** \mathcal{I} (written as $\mathcal{I} \models \varphi$) according to the following definition:

$\mathcal{I} \models a$	iff	$\mathcal{I}(a) = 1$	(for $a \in A$)
$\mathcal{I} \models \neg\varphi$	iff	not $\mathcal{I} \models \varphi$	
$\mathcal{I} \models (\varphi \wedge \psi)$	iff	$\mathcal{I} \models \varphi$ and $\mathcal{I} \models \psi$	
$\mathcal{I} \models (\varphi \vee \psi)$	iff	$\mathcal{I} \models \varphi$ or $\mathcal{I} \models \psi$	

Question: should we define semantics of $(\varphi \rightarrow \psi)$ and $(\varphi \leftrightarrow \psi)$?

German: Wahrheitsbelegung/Interpretation, φ gilt unter \mathcal{I}

Semantics of Propositional Logic: Terminology

- For $\mathcal{I} \models \varphi$ we also say \mathcal{I} is a model of φ and that φ is true under \mathcal{I} .
- If φ does not hold under \mathcal{I} , we write this as $\mathcal{I} \not\models \varphi$ and say that \mathcal{I} is no model of φ and that φ is false under \mathcal{I} .
- **Note:** \models is not part of the formula but part of the meta language (speaking about a formula).

German: \mathcal{I} ist ein/kein Modell von φ ; φ ist wahr/falsch unter \mathcal{I} ;
Metasprache

Exercise

Consider set $A = \{X, Y, Z\}$ of atomic propositions and formula $\varphi = (X \wedge \neg Y)$.

Specify an interpretation \mathcal{I} for A with $\mathcal{I} \models \varphi$.

Semantics: Example (1)

$$A = \{\text{DrinkBeer}, \text{EatFish}, \text{EatIceCream}\}$$

$$\mathcal{I} = \{\text{DrinkBeer} \mapsto 1, \text{EatFish} \mapsto 0, \text{EatIceCream} \mapsto 1\}$$

$$\varphi = (\neg \text{DrinkBeer} \rightarrow \text{EatFish})$$

Do we have $\mathcal{I} \models \varphi$?

Semantics: Example (2)

Goal: prove $\mathcal{I} \models \varphi$.

Let us use the definitions we have seen:

$$\begin{aligned}\mathcal{I} \models \varphi &\text{ iff } \mathcal{I} \models (\neg\text{DrinkBeer} \rightarrow \text{EatFish}) \\ &\text{ iff } \mathcal{I} \models (\neg\neg\text{DrinkBeer} \vee \text{EatFish}) \\ &\text{ iff } \mathcal{I} \models \neg\neg\text{DrinkBeer} \text{ or } \mathcal{I} \models \text{EatFish}\end{aligned}$$

This means that if we want to prove $\mathcal{I} \models \varphi$, it is sufficient to prove

$$\mathcal{I} \models \neg\neg\text{DrinkBeer}$$

or to prove

$$\mathcal{I} \models \text{EatFish}.$$

We attempt to prove the first of these statements.

Semantics: Example (3)

New goal: prove $\mathcal{I} \models \neg\neg\text{DrinkBeer}$.

We again use the definitions:

$$\begin{aligned}\mathcal{I} \models \neg\neg\text{DrinkBeer} &\text{ iff not } \mathcal{I} \models \neg\text{DrinkBeer} \\ &\text{ iff not not } \mathcal{I} \models \text{DrinkBeer} \\ &\text{ iff } \mathcal{I} \models \text{DrinkBeer} \\ &\text{ iff } \mathcal{I}(\text{DrinkBeer}) = 1\end{aligned}$$

The last statement is true for our interpretation \mathcal{I} .

To write this up as a **proof** of $\mathcal{I} \models \varphi$,
we can go through this line of reasoning back-to-front,
starting from our assumptions and ending with the conclusion
we want to show.

Semantics: Example (4)

Let $\mathcal{I} = \{\text{DrinkBeer} \mapsto 1, \text{EatFish} \mapsto 0, \text{EatIceCream} \mapsto 1\}$.

Proof that $\mathcal{I} \models (\neg\text{DrinkBeer} \rightarrow \text{EatFish})$:

- ① We have $\mathcal{I} \models \text{DrinkBeer}$
(uses defn. of \models for atomic props. and fact $\mathcal{I}(\text{DrinkBeer}) = 1$).
- ② From (1), we get $\mathcal{I} \not\models \neg\text{DrinkBeer}$
(uses defn. of \models for negations).
- ③ From (2), we get $\mathcal{I} \models \neg\neg\text{DrinkBeer}$
(uses defn. of \models for negations).
- ④ From (3), we get $\mathcal{I} \models (\neg\neg\text{DrinkBeer} \vee \psi)$ for all formulas ψ ,
in particular $\mathcal{I} \models (\neg\neg\text{DrinkBeer} \vee \text{EatFish})$
(uses defn. of \models for disjunctions).
- ⑤ From (4), we get $\mathcal{I} \models (\neg\text{DrinkBeer} \rightarrow \text{EatFish})$
(uses defn. of “ \rightarrow ”).



Summary

- **propositional logic** based on atomic propositions
- **syntax** defines what well-formed formulas are
- **semantics** defines when a formula is true
- **interpretations** are the basis of semantics