

Discrete Mathematics in Computer Science

B8. Functions

Malte Helmert, Gabriele Röger

University of Basel

October 25/30, 2023

Partial and Total Functions

Important Building Blocks of Discrete Mathematics

Important building blocks:

- sets
- relations
- **functions**

Important Building Blocks of Discrete Mathematics

Important building blocks:

- sets
- relations
- **functions**


In principle, functions are just a special kind of relations:

- $f : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $f(x) = x^2$
- relation R over \mathbb{N}_0 with $R = \{(x, x^2) \mid x \in \mathbb{N}_0\}$.


Functional Relations

Definition

A binary relation R over sets A and B is **functional** if for every $a \in A$ there is at most one $b \in B$ with $(a, b) \in R$.



functional



not functional

Functions – Examples

- $f : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $f(x) = x^2 + 1$

Functions – Examples

■ $f : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $f(x) = x^2 + 1$

■ $abs : \mathbb{Z} \rightarrow \mathbb{N}_0$ with

$$abs(x) = \begin{cases} x & \text{if } x \geq 0 \\ -x & \text{otherwise} \end{cases}$$

Functions – Examples

■ $f : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $f(x) = x^2 + 1$

■ $abs : \mathbb{Z} \rightarrow \mathbb{N}_0$ with

$$abs(x) = \begin{cases} x & \text{if } x \geq 0 \\ -x & \text{otherwise} \end{cases}$$

■ $distance : \mathbb{R}^2 \times \mathbb{R}^2 \rightarrow \mathbb{R}$ with

$$distance((x_1, y_1), (x_2, y_2)) = \sqrt{(x_2 - x_1)^2 + (y_2 - y_1)^2}$$

Partial Function – Example

Partial function $r : \mathbb{Z} \times \mathbb{Z} \rightarrow \mathbb{Q}$ with

$$r(n, d) = \begin{cases} \frac{n}{d} & \text{if } d \neq 0 \\ \text{undefined} & \text{otherwise} \end{cases}$$

Partial Functions

Definition (Partial function)

A **partial function** f from set A to set B (written $f : A \rightarrow B$) is given by a **functional relation** G over A and B .

Partial Functions

Definition (Partial function)

A **partial function** f from set A to set B (written $f : A \rightarrow B$) is given by a **functional relation** G over A and B .

Relation G is called the **graph** of f .

Partial Functions

Definition (Partial function)

A **partial function** f from set A to set B (written $f : A \rightarrow B$) is given by a **functional relation** G over A and B .

Relation G is called the **graph** of f .

We write $f(x) = y$ for $(x, y) \in G$ and say **y is the image of x under f** .

If there is no $y \in B$ with $(x, y) \in G$, then **$f(x)$ is undefined**.

Partial Functions

Definition (Partial function)

A **partial function** f from set A to set B (written $f : A \dashrightarrow B$) is given by a **functional relation** G over A and B .

Relation G is called the **graph** of f .

We write $f(x) = y$ for $(x, y) \in G$ and say **y is the image of x under f** .

If there is no $y \in B$ with $(x, y) \in G$, then **$f(x)$ is undefined**.

Partial function $r : \mathbb{Z} \times \mathbb{Z} \dashrightarrow \mathbb{Q}$ with

$$r(n, d) = \begin{cases} \frac{n}{d} & \text{if } d \neq 0 \\ \text{undefined} & \text{otherwise} \end{cases}$$

has graph $\{((n, d), \frac{n}{d}) \mid n \in \mathbb{Z}, d \in \mathbb{Z} \setminus \{0\}\} \subseteq \mathbb{Z}^2 \times \mathbb{Q}$.

Domain (of Definition), Codomain, Image

Definition (domain of definition, codomain, image)

Let $f : A \rightarrow B$ be a partial function.


Set A is called the **domain** of f , set B is its **codomain**.

Domain (of Definition), Codomain, Image

Definition (domain of definition, codomain, image)

Let $f : A \rightarrow B$ be a partial function.

Set A is called the **domain** of f , set B is its **codomain**.



$$f : \{a, b, c, d, e\} \rightarrow \{1, 2, 3, 4\}$$

$$f(a) = 4, f(b) = 2, f(c) = 1, f(e) = 4$$

domain $\{a, b, c, d, e\}$

codomain $\{1, 2, 3, 4\}$

Domain (of Definition), Codomain, Image


Definition (domain of definition, codomain, image)

Let $f : A \rightarrow B$ be a partial function.

Set A is called the **domain** of f , set B is its **codomain**.

The **domain of definition** of f is the set

$$\text{dom}(f) = \{x \in A \mid \text{there is a } y \in B \text{ with } f(x) = y\}.$$



$$f : \{a, b, c, d, e\} \rightarrow \{1, 2, 3, 4\}$$

$$f(a) = 4, f(b) = 2, f(c) = 1, f(e) = 4$$

$$\text{domain } \{a, b, c, d, e\}$$

$$\text{codomain } \{1, 2, 3, 4\}$$

$$\text{domain of definition } \text{dom}(f) = \{a, b, c, e\}$$

Domain (of Definition), Codomain, Image

Definition (domain of definition, codomain, image)

Let $f : A \rightarrow B$ be a partial function.


Set A is called the **domain** of f , set B is its **codomain**.

The **domain of definition** of f is the set

$$\text{dom}(f) = \{x \in A \mid \text{there is a } y \in B \text{ with } f(x) = y\}.$$

The **image** (or **range**) of f is the set

$$\text{img}(f) = \{y \mid \text{there is an } x \in A \text{ with } f(x) = y\}.$$



$$f : \{a, b, c, d, e\} \rightarrow \{1, 2, 3, 4\}$$

$$f(a) = 4, f(b) = 2, f(c) = 1, f(e) = 4$$

$$\text{domain } \{a, b, c, d, e\}$$

$$\text{codomain } \{1, 2, 3, 4\}$$

$$\text{domain of definition } \text{dom}(f) = \{a, b, c, e\}$$

$$\text{image } \text{img}(f) = \{1, 2, 4\}$$

Preimage

The preimage contains all elements of the domain that are mapped to given elements of the codomain.

Definition (Preimage)

Let $f : A \rightarrow B$ be a partial function and let $Y \subseteq B$.

The **preimage of Y under f** is the set

$$f^{-1}[Y] = \{x \in A \mid f(x) \in Y\}.$$

Preimage


The preimage contains all elements of the domain that are mapped to given elements of the codomain.

Definition (Preimage)

Let $f : A \rightarrow B$ be a partial function and let $Y \subseteq B$.

The **preimage of Y under f** is the set

$$f^{-1}[Y] = \{x \in A \mid f(x) \in Y\}.$$



$$f^{-1}[\{1\}] =$$

$$f^{-1}[\{3\}] =$$

$$f^{-1}[\{4\}] =$$

$$f^{-1}[\{1, 2\}] =$$

Total Functions

Definition (Total function)

A **(total) function** $f : A \rightarrow B$ from set A to set B is a partial function from A to B such that **$f(x)$ is defined for all $x \in A$.**

Total Functions

Definition (Total function)

A **(total) function** $f : A \rightarrow B$ from set A to set B is a partial function from A to B such that **$f(x)$ is defined for all $x \in A$.**


→ no difference between the domain and the domain of definition

Total Functions

Definition (Total function)

A **(total) function** $f : A \rightarrow B$ from set A to set B is a partial function from A to B such that $f(x)$ is defined for all $x \in A$.

→ no difference between the domain and the domain of definition



Specifying a Function

Some common ways of specifying a function:

- Listing the mapping **explicitly**, e. g.

$$f(a) = 4, f(b) = 2, f(c) = 1, f(e) = 4 \text{ or}$$

$$f = \{a \mapsto 4, b \mapsto 2, c \mapsto 1, e \mapsto 4\}$$

Specifying a Function

Some common ways of specifying a function:

- Listing the mapping **explicitly**, e. g.

$$f(a) = 4, f(b) = 2, f(c) = 1, f(e) = 4 \text{ or}$$

$$f = \{a \mapsto 4, b \mapsto 2, c \mapsto 1, e \mapsto 4\}$$

- By a **formula**, e. g. $f(x) = x^2 + 1$

Specifying a Function

Some common ways of specifying a function:

- Listing the mapping **explicitly**, e. g.

$$f(a) = 4, f(b) = 2, f(c) = 1, f(e) = 4 \text{ or}$$

$$f = \{a \mapsto 4, b \mapsto 2, c \mapsto 1, e \mapsto 4\}$$

- By a **formula**, e. g. $f(x) = x^2 + 1$

- By **recurrence**, e. g.

$$0! = 1 \text{ and}$$

$$n! = n(n - 1)! \text{ for } n > 0$$

Specifying a Function

Some common ways of specifying a function:

- Listing the mapping **explicitly**, e. g.

$$f(a) = 4, f(b) = 2, f(c) = 1, f(e) = 4 \text{ or}$$

$$f = \{a \mapsto 4, b \mapsto 2, c \mapsto 1, e \mapsto 4\}$$

- By a **formula**, e. g. $f(x) = x^2 + 1$

- By **recurrence**, e. g.

$$0! = 1 \text{ and}$$

$$n! = n(n - 1)! \text{ for } n > 0$$

- In terms of other functions, e. g. inverse, composition

Relationship to Functions in Programming

```
def factorial(n):  
    if n == 0:  
        return 1  
    else:  
        return n * factorial(n-1)
```

→ Relationship between recursion and recurrence

Relationship to Functions in Programming

```
def foo(n):  
    value = ...  
    while <some condition>:  
        ...  
        value = ...  
    return value
```

- Does possibly not terminate on all inputs.
- Value is undefined for such inputs.
- Theoretical computer science: partial function

Relationship to Functions in Programming

```
import random
counter = 0

def bar(n):
    print("Hi! I got input", n)
    global counter
    counter += 1
    return random.choice([1,2,n])
```

- Functions in programming don't always compute mathematical functions (except *purely functional languages*).
- In addition, not all mathematical functions are computable.

Questions



Questions?

Operations on Partial Functions

Restrictions and Extensions

Definition (restriction and extension)

Let $f : A \rightarrow B$ be a partial function and let $X \subseteq A$.

The **restriction of f to X** is the partial function $f|_X : X \rightarrow B$ with $f|_X(x) = f(x)$ for all $x \in X$.

Restrictions and Extensions

Definition (restriction and extension)

Let $f : A \rightarrow B$ be a partial function and let $X \subseteq A$.

The **restriction of f to X** is the partial function $f|_X : X \rightarrow B$ with $f|_X(x) = f(x)$ for all $x \in X$.

A function $f' : A' \rightarrow B$ is called an **extension of f** if $A \subseteq A'$ and $f'|_A = f$.

Restrictions and Extensions

Definition (restriction and extension)

Let $f : A \rightrightarrows B$ be a partial function and let $X \subseteq A$.

The **restriction of f to X** is the partial function $f|_X : X \rightrightarrows B$ with $f|_X(x) = f(x)$ for all $x \in X$.

A function $f' : A' \rightrightarrows B$ is called an **extension of f** if $A \subseteq A'$ and $f'|_A = f$.

The restriction of f to its domain of definition is a total function.

Restrictions and Extensions

Definition (restriction and extension)

Let $f : A \rightrightarrows B$ be a partial function and let $X \subseteq A$.

The **restriction of f to X** is the partial function $f|_X : X \rightrightarrows B$ with $f|_X(x) = f(x)$ for all $x \in X$.

A function $f' : A' \rightrightarrows B$ is called an **extension of f** if $A \subseteq A'$ and $f'|_A = f$.

The restriction of f to its domain of definition is a total function.

What's the graph of the restriction?

Restrictions and Extensions

Definition (restriction and extension)

Let $f : A \rightarrow B$ be a partial function and let $X \subseteq A$.

The **restriction of f to X** is the partial function $f|_X : X \rightarrow B$ with $f|_X(x) = f(x)$ for all $x \in X$.

A function $f' : A' \rightarrow B$ is called an **extension of f** if $A \subseteq A'$ and $f'|_A = f$.

The restriction of f to its domain of definition is a total function.

What's the graph of the restriction?

What's the restriction of f to its domain?

Function Composition

Definition (Composition of partial functions)

Let $f : A \dashrightarrow B$ and $g : B \dashrightarrow C$ be partial functions.

The **composition of f and g** is $g \circ f : A \dashrightarrow C$ with

$$(g \circ f)(x) = \begin{cases} g(f(x)) & \text{if } f \text{ is defined for } x \text{ and} \\ & g \text{ is defined for } f(x) \\ \text{undefined} & \text{otherwise} \end{cases}$$

Function Composition

Definition (Composition of partial functions)

Let $f : A \dashrightarrow B$ and $g : B \dashrightarrow C$ be partial functions.

The **composition of f and g** is $g \circ f : A \dashrightarrow C$ with

$$(g \circ f)(x) = \begin{cases} g(f(x)) & \text{if } f \text{ is defined for } x \text{ and} \\ & g \text{ is defined for } f(x) \\ \text{undefined} & \text{otherwise} \end{cases}$$

Corresponds to relation composition of the graphs.

Function Composition

Definition (Composition of partial functions)

Let $f : A \dashrightarrow B$ and $g : B \dashrightarrow C$ be partial functions.

The **composition of f and g** is $g \circ f : A \dashrightarrow C$ with

$$(g \circ f)(x) = \begin{cases} g(f(x)) & \text{if } f \text{ is defined for } x \text{ and} \\ & g \text{ is defined for } f(x) \\ \text{undefined} & \text{otherwise} \end{cases}$$

Corresponds to relation composition of the graphs.

If f and g are functions, their composition is a function.

Function Composition

Definition (Composition of partial functions)

Let $f : A \dashrightarrow B$ and $g : B \dashrightarrow C$ be partial functions.

The **composition of f and g** is $g \circ f : A \dashrightarrow C$ with

$$(g \circ f)(x) = \begin{cases} g(f(x)) & \text{if } f \text{ is defined for } x \text{ and} \\ & g \text{ is defined for } f(x) \\ \text{undefined} & \text{otherwise} \end{cases}$$

Corresponds to relation composition of the graphs.

If f and g are functions, their composition is a function.

Example:

$$f : \mathbb{N}_0 \rightarrow \mathbb{N}_0 \quad \text{with } f(x) = x^2$$

$$g : \mathbb{N}_0 \rightarrow \mathbb{N}_0 \quad \text{with } g(x) = x + 3$$

$$(g \circ f)(x) =$$

Properties of Function Composition

Function composition is

- **not commutative:**

Properties of Function Composition

Function composition is

- **not commutative:**

- $f : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $f(x) = x^2$

Properties of Function Composition

Function composition is

- **not commutative:**

- $f : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $f(x) = x^2$
- $g : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $g(x) = x + 3$

Properties of Function Composition

Function composition is

- **not commutative:**

- $f : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $f(x) = x^2$
- $g : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $g(x) = x + 3$
- $(g \circ f)(x) = x^2 + 3$

Properties of Function Composition

Function composition is

- **not commutative:**

- $f : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $f(x) = x^2$
- $g : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $g(x) = x + 3$
- $(g \circ f)(x) = x^2 + 3$
- $(f \circ g)(x) = (x + 3)^2$

Properties of Function Composition

Function composition is

- **not commutative:**

- $f : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $f(x) = x^2$
- $g : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $g(x) = x + 3$
- $(g \circ f)(x) = x^2 + 3$
- $(f \circ g)(x) = (x + 3)^2$

- **associative**, i. e. $h \circ (g \circ f) = (h \circ g) \circ f$

→ analogous to associativity of relation composition

Function Composition in Programming

We implicitly compose functions all the time...

```
def foo(n):  
    ...  
    x = somefunction(n)  
    y = someotherfunction(x)  
    ...
```

Function Composition in Programming

We implicitly compose functions all the time...

```
def foo(n):  
    ...  
    x = somefunction(n)  
    y = someotherfunction(x)  
    ...
```

Many languages also allow explicit composition of functions, e.g. in Haskell:

```
incr x = x + 1  
square x = x * x  
squareplusone = incr . square
```



Questions



Questions?


Properties of Functions

Properties of Functions




- Partial functions map every element of their domain to at most one element of their codomain, total functions map it to exactly one such value.

Properties of Functions




- Partial functions map every element of their domain to at most one element of their codomain, total functions map it to exactly one such value.
- Different elements of the domain can have the same image.

Properties of Functions



- Partial functions map every element of their domain to at most one element of their codomain, total functions map it to exactly one such value.
- Different elements of the domain can have the same image.
- There can be values of the codomain that aren't the image of any element of the domain.

Properties of Functions





- Partial functions map every element of their domain to at most one element of their codomain, total functions map it to exactly one such value.
- Different elements of the domain can have the same image.
- There can be values of the codomain that aren't the image of any element of the domain.
- We often want to exclude such cases
→ define additional properties to say this quickly

Injective Functions

An **injective function** maps distinct elements of its domain to distinct elements of its co-domain.

Definition (Injective Function)

A function $f : A \rightarrow B$ is **injective** (also **one-to-one** or an **injection**) if for all $x, y \in A$ with $x \neq y$ it holds that $f(x) \neq f(y)$.



Injective Functions – Examples

Which of these functions are injective?

- $f : \mathbb{Z} \rightarrow \mathbb{N}_0$ with $f(x) = |x|$

- $g : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $g(x) = x^2$

- $h : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $h(x) = \begin{cases} x - 1 & \text{if } x \text{ is odd} \\ x + 1 & \text{if } x \text{ is even} \end{cases}$

Composition of Injective Functions

Theorem

If $f : A \rightarrow B$ and $g : B \rightarrow C$ are injective functions then also $g \circ f$ is injective.

Composition of Injective Functions

Theorem

If $f : A \rightarrow B$ and $g : B \rightarrow C$ are injective functions then also $g \circ f$ is injective.

Proof.

Consider arbitrary elements $x, y \in A$ with $x \neq y$.

Since f is injective, we know that $f(x) \neq f(y)$.

As g is injective, this implies that $g(f(x)) \neq g(f(y))$.

With the definition of $g \circ f$, we conclude that

$(g \circ f)(x) \neq (g \circ f)(y)$.



Overall, this shows that $g \circ f$ is injective. □

Surjective Functions

A **surjective function** maps at least one element to every element of its co-domain.

Definition (Surjective Function)

A function $f : A \rightarrow B$ is **surjective** (also **onto** or a **surjection**) if its **image is equal to its codomain**,
i. e. for all $y \in B$ there is an $x \in A$ with $f(x) = y$.



Surjective Functions – Examples

Which of these functions are surjective?

■ $f : \mathbb{Z} \rightarrow \mathbb{N}_0$ with $f(x) = |x|$

■ $g : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $g(x) = x^2$

■ $h : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $h(x) = \begin{cases} x - 1 & \text{if } x \text{ is odd} \\ x + 1 & \text{if } x \text{ is even} \end{cases}$

Composition of Surjective Functions

Theorem

If $f : A \rightarrow B$ and $g : B \rightarrow C$ are surjective functions then also $g \circ f$ is surjective.

Composition of Surjective Functions

Theorem

If $f : A \rightarrow B$ and $g : B \rightarrow C$ are surjective functions then also $g \circ f$ is surjective.

Proof.

Consider an arbitrary element $z \in C$.

Since g is surjective, there is a $y \in B$ with $g(y) = z$.

As f is surjective, for such a y there is an $x \in A$ with $f(x) = y$ and thus $g(f(x)) = z$.

Overall, for every $z \in C$ there is an $x \in A$ with $(g \circ f)(x) = g(f(x)) = z$, so $g \circ f$ is surjective. □

Questions



Questions?

Bijjective Functions

A **bijjective function** pairs every element of its domain with exactly one element of its codomain and every element of the codomain is paired with exactly one element of the domain.

Definition (Bijjective Function)


A function is **bijjective** (also a **one-to-one correspondence** or a **bijjection**) if it is **injective and surjective**.

Bijjective Functions

A **bijjective function** pairs every element of its domain with exactly one element of its codomain and every element of the codomain is paired with exactly one element of the domain.

Definition (Bijjective Function)

A function is **bijjective** (also a **one-to-one correspondence** or a **bijection**) if it is **injective** and **surjective**.




Bijjective Functions

A **bijjective function** pairs every element of its domain with exactly one element of its codomain and every element of the codomain is paired with exactly one element of the domain.

Definition (Bijjective Function)

A function is **bijjective** (also a **one-to-one correspondence** or a **bijjection**) if it is **injective and surjective**.



Corollary

The composition of two bijective functions is bijective.

Bijjective Functions – Examples

Which of these functions are bijective?

- $f : \mathbb{Z} \rightarrow \mathbb{N}_0$ with $f(x) = |x|$

- $g : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $g(x) = x^2$

- $h : \mathbb{N}_0 \rightarrow \mathbb{N}_0$ with $h(x) = \begin{cases} x - 1 & \text{if } x \text{ is odd} \\ x + 1 & \text{if } x \text{ is even} \end{cases}$

Inverse Function

Definition

Let $f : A \rightarrow B$ be a bijection.



The **inverse function** of f is the function $f^{-1} : B \rightarrow A$ with $f^{-1}(y) = x$ iff $f(x) = y$.

Inverse Function

Definition

Let $f : A \rightarrow B$ be a bijection.

The **inverse function** of f is the function $f^{-1} : B \rightarrow A$ with $f^{-1}(y) = x$ iff $f(x) = y$.



Inverse Function and Composition

Theorem

Let $f : A \rightarrow B$ be a bijection.

- 1 For all $x \in A$ it holds that $f^{-1}(f(x)) = x$.
- 2 For all $y \in B$ it holds that $f(f^{-1}(y)) = y$.
- 3 f^{-1} is a bijection from B to A .
- 4 $(f^{-1})^{-1} = f$

Inverse Function and Composition

Theorem

Let $f : A \rightarrow B$ be a bijection.

- 1 For all $x \in A$ it holds that $f^{-1}(f(x)) = x$.
- 2 For all $y \in B$ it holds that $f(f^{-1}(y)) = y$.
- 3 f^{-1} is a bijection from B to A .
- 4 $(f^{-1})^{-1} = f$

Proof sketch.

- 1 For $x \in A$ let $y = f(x)$. Then $f^{-1}(f(x)) = f^{-1}(y) = x$
- 2 For $y \in B$ there is exactly one x with $y = f(x)$. With this x it holds that $f^{-1}(y) = x$ and overall $f(f^{-1}(y)) = f(x) = y$.

Inverse Function and Composition

Theorem

Let $f : A \rightarrow B$ be a bijection.

- 1 For all $x \in A$ it holds that $f^{-1}(f(x)) = x$.
- 2 For all $y \in B$ it holds that $f(f^{-1}(y)) = y$.
- 3 f^{-1} is a bijection from B to A .
- 4 $(f^{-1})^{-1} = f$

Proof sketch.

- 1 For $x \in A$ let $y = f(x)$. Then $f^{-1}(f(x)) = f^{-1}(y) = x$
- 2 For $y \in B$ there is exactly one x with $y = f(x)$. With this x it holds that $f^{-1}(y) = x$ and overall $f(f^{-1}(y)) = f(x) = y$.
- 3 Surjective: for all $x \in A$, f^{-1} maps $f(x)$ to x (cf. (1)).
Injective: if $f^{-1}(y) = f^{-1}(y')$ then $f(f^{-1}(y)) = f(f^{-1}(y'))$, so with (2) we have $y = y'$.

Inverse Function and Composition

Theorem

Let $f : A \rightarrow B$ be a bijection.

- 1 For all $x \in A$ it holds that $f^{-1}(f(x)) = x$.
- 2 For all $y \in B$ it holds that $f(f^{-1}(y)) = y$.
- 3 f^{-1} is a bijection from B to A .
- 4 $(f^{-1})^{-1} = f$

Proof sketch.

- 1 For $x \in A$ let $y = f(x)$. Then $f^{-1}(f(x)) = f^{-1}(y) = x$
- 2 For $y \in B$ there is exactly one x with $y = f(x)$. With this x it holds that $f^{-1}(y) = x$ and overall $f(f^{-1}(y)) = f(x) = y$.
- 3 Surjective: for all $x \in A$, f^{-1} maps $f(x)$ to x (cf. (1)).
Injective: if $f^{-1}(y) = f^{-1}(y')$ then $f(f^{-1}(y)) = f(f^{-1}(y'))$, so with (2) we have $y = y'$.
- 4 Def. of inverse: $(f^{-1})^{-1}(x) = y$ iff $f^{-1}(y) = x$ iff $f(x) = y$.

Inverse Function

Theorem

Let $f : A \rightarrow B$ and $g : B \rightarrow C$ be bijections.

Then $(g \circ f)^{-1} = f^{-1} \circ g^{-1}$.

Inverse Function

Theorem

Let $f : A \rightarrow B$ and $g : B \rightarrow C$ be bijections.

Then $(g \circ f)^{-1} = f^{-1} \circ g^{-1}$.

Proof.

We need to show that for all $x \in C$ it holds that

$$(g \circ f)^{-1}(x) = (f^{-1} \circ g^{-1})(x).$$

Consider an arbitrary $x \in C$ and let $y = (g \circ f)^{-1}(x)$.

By the definition of the inverse $(g \circ f)(y) = g(f(y)) = x$.

Let $z = f(y)$.

From $x = g(f(y))$, we know that $x = g(z)$ and thus $g^{-1}(x) = z$.

From $z = f(y)$ we get $f^{-1}(z) = y$.



This gives $(f^{-1} \circ g^{-1})(x) = f^{-1}(g^{-1}(x)) = f^{-1}(z) = y$. □

Questions



Questions?

Permutations



Permutations as Functions

- A **permutation** rearranges objects.

Permutations as Functions

- A **permutation** rearranges objects.
- Consider for example sequence o_2, o_1, o_3, o_4

Permutations as Functions

- A **permutation** rearranges objects.
- Consider for example sequence o_2, o_1, o_3, o_4
- Let's rearrange the objects, e. g. to o_3, o_1, o_4, o_2 .

Permutations as Functions

- A **permutation** rearranges objects.
- Consider for example sequence o_2, o_1, o_3, o_4
- Let's rearrange the objects, e. g. to o_3, o_1, o_4, o_2 .
 - The object at position 1 was moved to position 4,

Permutations as Functions

- A **permutation** rearranges objects.
- Consider for example sequence o_2, o_1, o_3, o_4
- Let's rearrange the objects, e. g. to o_3, o_1, o_4, o_2 .
 - The object at position 1 was moved to position 4,
 - the one from position 3 to position 1,

Permutations as Functions

- A **permutation** rearranges objects.
- Consider for example sequence o_2, o_1, o_3, o_4
- Let's rearrange the objects, e. g. to o_3, o_1, o_4, o_2 .
 - The object at position 1 was moved to position 4,
 - the one from position 3 to position 1,
 - the one from position 4 to position 3 and

Permutations as Functions

- A **permutation** rearranges objects.
- Consider for example sequence o_2, o_1, o_3, o_4
- Let's rearrange the objects, e. g. to o_3, o_1, o_4, o_2 .
 - The object at position 1 was moved to position 4,
 - the one from position 3 to position 1,
 - the one from position 4 to position 3 and
 - the one at position 2 stayed where it was.

Permutations as Functions

- A **permutation** rearranges objects.
- Consider for example sequence o_2, o_1, o_3, o_4
- Let's rearrange the objects, e. g. to o_3, o_1, o_4, o_2 .
 - The object at position 1 was moved to position 4,
 - the one from position 3 to position 1,
 - the one from position 4 to position 3 and
 - the one at position 2 stayed where it was.
- This corresponds to a **bijection** $\sigma : \{1, 2, 3, 4\} \rightarrow \{1, 2, 3, 4\}$ with $\sigma(1) = 4, \sigma(2) = 2, \sigma(3) = 1, \sigma(4) = 3$

Permutations as Functions

- A **permutation** rearranges objects.
- Consider for example sequence o_2, o_1, o_3, o_4
- Let's rearrange the objects, e. g. to o_3, o_1, o_4, o_2 .
 - The object at position 1 was moved to position 4,
 - the one from position 3 to position 1,
 - the one from position 4 to position 3 and
 - the one at position 2 stayed where it was.
- This corresponds to a **bijection** $\sigma : \{1, 2, 3, 4\} \rightarrow \{1, 2, 3, 4\}$ with $\sigma(1) = 4, \sigma(2) = 2, \sigma(3) = 1, \sigma(4) = 3$
- We call such a bijection a **permutation**.

Permutation – Definition

Definition (Permutation)

Let S be a set. A **bijection** $\pi : S \rightarrow S$ is called a **permutation of S** .

Permutation – Definition

Definition (Permutation)

Let S be a set. A **bijection** $\pi : S \rightarrow S$ is called a **permutation of S** .

How many permutations are there for a finite set S ?

Permutation – Definition

Definition (Permutation)

Let S be a set. A **bijection** $\pi : S \rightarrow S$ is called a **permutation of S** .

How many permutations are there for a finite set S ?

Permutations of the same set S can be composed with function composition. The result is again a permutation of S . Why?

Permutation – Definition

Definition (Permutation)

Let S be a set. A **bijection** $\pi : S \rightarrow S$ is called a **permutation of S** .

How many permutations are there for a finite set S ?

Permutations of the same set S can be composed with function composition. The result is again a permutation of S . Why?



The inverse of a permutation is again a permutation.

Permutation: Example I

Describe what fruit is moved to the place of what fruit, independent of the positions.



Permutation: Example 1

Describe what fruit is moved to the place of what fruit, independent of the positions.

Swap the  and the  with permutation f of $\{\text{pear}, \text{apple}, \text{orange}\}$ with $f(\text{pear}) = \text{apple}$, $f(\text{apple}) = \text{pear}$, $f(\text{orange}) = \text{orange}$.

Permutation: Example 1



Describe what fruit is moved to the place of what fruit, independent of the positions.

Swap the  and the  with permutation f of $\{\text{pear}, \text{apple}, \text{orange}\}$ with $f(\text{pear}) = \text{apple}$, $f(\text{apple}) = \text{pear}$, $f(\text{orange}) = \text{orange}$.




If g maps locations to fruits then $f^{-1} \circ g$ describes the mapping from locations to fruits after the swap.




Permutation: Example 1

Describe what fruit is moved to the place of what fruit, independent of the positions.

Swap the  and the  with permutation f of $\{\text{pear}, \text{apple}, \text{orange}\}$ with $f(\text{pear}) = \text{apple}$, $f(\text{apple}) = \text{pear}$, $f(\text{orange}) = \text{orange}$.

If g maps locations to fruits then $f^{-1} \circ g$ describes the mapping from locations to fruits after the swap.

For example $g(1) = \text{pear}$, $g(2) = \text{apple}$, $g(3) = \text{orange}$ for .




Then $(f^{-1} \circ g)(1) = \text{apple}$, $(f^{-1} \circ g)(2) = \text{pear}$, $(f^{-1} \circ g)(3) = \text{orange}$ representing .

Permutation: Example II

Determine the arrangement of some objects after applying a permutation that operates on the locations.




Permutation: Example II

Determine the arrangement of some objects after applying a permutation that operates on the locations.

   and π permutation of $\{1, 2, 3\}$.

Permutation: Example II



Determine the arrangement of some objects after applying a permutation that operates on the locations.

   and π permutation of $\{1, 2, 3\}$.

Define f with $f(\text{pear}) = 1$, $f(\text{apple}) = 2$, $f(\text{orange}) = 3$ to describe the initial configuration.

Permutation: Example II

Determine the arrangement of some objects after applying a permutation that operates on the locations.

   and π permutation of $\{1, 2, 3\}$.

Define f with $f(\text{pear}) = 1$, $f(\text{apple}) = 2$, $f(\text{orange}) = 3$ to describe the initial configuration.

Then $\pi \circ f$ describes the resulting configuration.

Permutation: Example III

Determine the permutation of locations that leads from one configuration to the other.

Permutation: Example III

Determine the permutation of locations that leads from one configuration to the other.



Permutation: Example III

Determine the permutation of locations that leads from one configuration to the other.



Define f with $f(\text{pear}) = 1$, $f(\text{apple}) = 2$, $f(\text{orange}) = 3$
to describe the initial configuration and

function g with $g(\text{pear}) = 2$, $g(\text{apple}) = 1$, $g(\text{orange}) = 3$
for the final configuration.

Permutation: Example III

Determine the permutation of locations that leads from one configuration to the other.



Define f with $f(\text{pear}) = 1$, $f(\text{apple}) = 2$, $f(\text{orange}) = 3$
to describe the initial configuration and

function g with $g(\text{pear}) = 2$, $g(\text{apple}) = 1$, $g(\text{orange}) = 3$
for the final configuration.

Then $g \circ f^{-1}$ describes the permutation of locations.

Questions



Questions?

Summary

- **injective function**: maps distinct elements of its domain to distinct elements of its co-domain.
- **surjective function**: maps at least one element to every element of its co-domain.
- **bijective function**: injective and surjective
→ one-to-one correspondence
- Bijective functions are invertible. The **inverse** function of f maps the image of x under f to x .
- **Permutations** are bijections from a set to itself. They can be used to describe rearrangements of objects.