Planning and Optimization

D1. Delete Relaxation: Relaxed Planning Tasks

Malte Helmert and Gabriele Röger

Universität Basel

October 19, 2026

D1.1 Heuristics

D1.2 Coming Up with Heuristics

D1.3 Relaxed Planning Tasks

D1.4 Summary

Content of the Course



D1.1 Heuristics

Planning as Heuristic Search

- Heuristic search is the most common approach to planning.
- ingredients: general search algorithm + heuristic
- heuristic estimates cost from a given state to a given goal
  - progression: from varying states s to fixed goal γ
  - regression: from fixed initial state I to varying subgoals φ
- Over the next weeks, we study the main ideas behind heuristics for planning tasks.

Reminder: Heuristics

Need to Catch Up?

- We assume familiarity with heuristics and their properties:
  - heuristic $h : S \to \mathbb{R}_0^+ \cup \{\infty\}$
  - perfect heuristic h^*: $h^*(s)$ cost of optimal solution from s (∞ if unsolvable)
  - properties of heuristics h:
    - safe: $(h(s) = \infty \Rightarrow h^*(s) = \infty)$ for all states s
    - goal-aware: $h(s) = 0$ for all goal states s
    - admissible: $h(s) \leq h^*(s)$ for all states s
    - consistent: $h(s) \leq cost(o) + h(s')$ for all transitions $s \xrightarrow{o} s'$
  - connections between these properties
- If you are not familiar with these, we recommend Ch. B9–B10 of the Foundations of Artificial Intelligence course: `https://dmi.unibas.ch/en/studies/computer-science/course-offer-spring-2026/13548-lecture-foundations-of-artificial-intelligence/`

D1.2 Coming Up with Heuristics

A Simple Heuristic for Propositional Planning Tasks

STRIPS (Fikes & Nilsson, 1971) used the number of state variables that differ in current state s and a STRIPS goal $v_1 \wedge \cdots \wedge v_n$:

$$h(s) := |\{i \in \{1, \dots, n\} \mid s \not\models v_i\}|.$$

Intuition: more satisfied goal atoms $\rightsquigarrow$ closer to the goal

$\rightsquigarrow$ STRIPS heuristic (a.k.a. goal-count heuristic)

Criticism of the STRIPS Heuristic

What is wrong with the STRIPS heuristic?

- quite uninformative:
  the range of heuristic values in a given task is small;
  typically, most successors have the same estimate
- very sensitive to reformulation:
  can easily transform any planning task into an equivalent one where $h(s) = 1$ for all non-goal states (how?)
- ignores almost all problem structure:
  heuristic value does not depend on the set of operators!

$\rightsquigarrow$ need a better, principled way of coming up with heuristics

Coming Up with Heuristics in a Principled Way

General Procedure for Obtaining a Heuristic

- Simplify the problem, for example by removing problem constraints.
- Solve the simplified problem (ideally optimally).
- Use the solution cost for the simplified problem as a heuristic for the real problem.

As heuristic values are computed for every generated search state, it is important that they can be computed efficiently.

Relaxing a Problem: Example

Example (Route Planning in a Road Network)

The road network is formalized as a weighted graph over points in the Euclidean plane. The weight of an edge is the road distance between two locations.

Example (Relaxation for Route Planning)

Use the Euclidean distance $\sqrt{|x_1 - x_2|^2 + |y_1 - y_2|^2}$ as a heuristic for the road distance between $\langle x_1, y_1 \rangle$ and $\langle x_2, y_2 \rangle$
This is a lower bound on the road distance ($\rightsquigarrow$ admissible).

$\rightsquigarrow$ We drop the constraint of having to travel on roads.

Planning Heuristics: Main Concepts

Major ideas for heuristics in the planning literature:

- delete relaxation $\rightsquigarrow$ Part D
- abstraction $\rightsquigarrow$ Part E
- critical paths $\rightsquigarrow$ not considered in this course
- landmarks $\rightsquigarrow$ Part F
- network flows $\rightsquigarrow$ Part F
- potential heuristics $\rightsquigarrow$ Part F

We will consider most of them in this course.

D1.3 Relaxed Planning Tasks

Content of the Course



Delete Relaxation: Idea

In positive normal form (Chapter B5, remember?), good and bad effects are easy to distinguish*:

- Effects that make state variables true are good (add effects).
- Effects that make state variables false are bad (delete effects).

Idea of delete relaxation heuristics: ignore all delete effects.

(*) with a small caveat regarding conditional effects

Delete-Relaxed Planning Tasks

Definition (Delete Relaxation of Operators)

The delete relaxation o^+ of an operator o in positive normal form is the operator obtained by replacing all negative effects $\neg a$ within $\mathit{eff}(o)$ by the do-nothing effect $\top$.

Definition (Delete Relaxation of Propositional Planning Tasks)

The delete relaxation Π^+ of a propositional planning task $\Pi = \langle V, I, O, \gamma \rangle$ in positive normal form is the planning task $\Pi^+ := \langle V, I, \{o^+ \mid o \in O\}, \gamma \rangle$.

Definition (Delete Relaxation of Operator Sequences)

The delete relaxation of an operator sequence $\pi = \langle o_1, \dots, o_n \rangle$ is the operator sequence $\pi^+ := \langle o_1^+, \dots, o_n^+ \rangle$.

Note: "delete" is often omitted: relaxation, relaxed

Relaxed Planning Tasks: Terminology

- Planning tasks in positive normal form without delete effects are called relaxed planning tasks.
- Plans for relaxed planning tasks are called relaxed plans.
- If Π is a planning task in positive normal form and π^+ is a plan for Π^+, then π^+ is called a relaxed plan for Π.

D1.4 Summary

Summary

- A general way to come up with heuristics: solve a simplified version of the real problem, for example by removing problem constraints.
- delete relaxation: given a task in positive normal form, discard all delete effects